

## TECHNICAL SPECIFICATION ALARM Cable

Italian Conductors, Wires & Cables

### CABLE DESCRIPTION

**Conductor:** Flexible bare copper conductor

**Insulation:** PVC EN 50363-3 Type TI2

**Colour code:** see table below

**Assembly:** conductors with polyester tape, drain wire bare copper 7x0.15mm and aluminium/polyester tape

**Sheath:** PVC EN 50363-4-1 Type TM2 White Ral 9003

**Marking:** EUROCAVI nxsize CPR 305/2011 Class Eca ITC006E-E n°week/year

**Temperature range:** -5°C up to+70°C

**Working voltage:** 250 V

**Test voltage:** 1000 V

**Standard:**

CPR 305/2011 EN 50575:2014 +A1:2016 Class Eca

### DIMENSIONAL CHARACTERISTICS

Number of conductor	Section (mm <sup>2</sup> )	N° and Diameter of wire (mm)	Insulation thickness (mm)	Diameter of conductors (mm)	Outer diameter (mm)	Insulation sheath (mm)	Cu weight (kg/km)	Approx Cable weight (kg/km)
2	0.22	7x0.15	0.25	1.00±0.05	3.10±0.20	0.60	4.08	14.00
4					3.90±0.20	0.60	6.80	20.00
6					4.40±0.20	0.60	9.52	24.00
8					4.80±0.20	0.60	12.24	35.00
10					5.20±0.20	0.60	14.96	40.00
12					5.40±0.20	0.70	17.68	48.00
14					5.80±0.20	0.70	20.40	55.00
16					6.20±0.20	0.70	23.12	58.00
20					7.00±0.20	0.70	28.56	62.00
24					7.40±0.20	0.70	34.00	66.00

## TECHNICAL SPECIFICATION ALARM Cable

Italian Conductors, Wires & Cables

Number of conductor	Section (mm <sup>2</sup> )	N° and Diameter of wire (mm)	Insulation thickness (mm)	Diameter of conductors (mm)	Outer diameter (mm)	Insulation sheath (mm)	Cu weight (kg/km)	Approx Cable weight (kg/km)
2+2	0.75/0.22	14x0.20 /7x0.15	0.48/0.28	1.70/1.00 ±0.05	4.70±0.20	0.70	11.91	38.00
2+4					5.00±0.20			
2+6					5.20±0.30			
2+8					6.00±0.30			
2+10					6.20±0.30			
2+12					6.60±0.30			
2+8	1.00/ 0.22	31x0.193/ 7x0.18	0.40/ 0.25	2.10/ 1.05±0.05	6.40±0.30	0.70	38.21	66.00
2+10	1.00/ 0.22	31x0.193/ 7x0.18	0.40/ 0.25	2.10/ 1.05±0.05	6.80±0.30	0.70	41.00	70.00
2+4	1.50/ 0.22	24x0.26/ 7x0.18	0.60/ 0.25	2.80/ 1.05±0.05	7.50±0.30	0.70	34.00	68.00

# TECHNICAL SPECIFICATION

## ALARM Cable

Italian Conductors, Wires & Cables

### COLOUR TABLE

Conductor	Colour
2x0.75	Red/Black
1/0.22	White
2	Red
3	Yellow
4	Green
5	Grey
6	Orange
7	L.Blue
8	Brown
9	Violet
10	Black
11	Blue
12	Pink
13	White/Brown
14	White/Violet
15	White/Green
16	White/Blue
17	White/Grey
18	White/Yellow
19	White/Black
20	White/Red

DATE OF ISSUE	Rev0 05/12/2018
TECHNICAL DEPT.	Napoli Giuseppe